BioMax®



SPEEDFACE - 5

Face | Touch Screen | RFID | WiFi | LAN | USB | Access Control

Facial Attendance and Access Control

Storage Capacity

Face ID Capacity	50,000
Card Capacity	50,000
Log Capacity	10,00,000



Features

- DualCoreARM Cortex-A7@900 MHZ Processor
- Remotely Firmware Upgradation.
- 5-inch IPS display all-sight LCD touch screen with 480*854 resolution.
- IP54 Grade Highly finished slim device.
- Highly reliable and durable
- Recognition speed 0.5 seconds

SpeedFace - 5

Communication Interface

Communication	WIFI, TCP/IP, USB

Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.0001%
FAR	0.1%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7 @900MHz
OS	Linux
Verification time	<=1 second
RF card options	Wiegand 26/34

Audio/Visual

LCD	5.0" IPS touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Access control

Relay	YES
Wiegand output	YES
Storage	2GB RAM, 16 GB ROM

Power & Environment

Operating Temperature	-10°c ~ 50°c
Power	12V DC / 2A
Dimension	190.00 x 87.53 x 17.00 mm

Auto Focus

low light Verification



Long Distance Verification

Software

Web & Cloud

Time Attendance

Access Control

Employee Self Service

Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by

www.biomaxsecurity.com

Connect with us on

BiomaxOfficial
BioMax Security
biomaxsecurity
BioMax Access Control